


NOTE:  
- LOAD VALUES DO NOT CONSIDER BRIDLE OR DEAD HANG LOADS BETWEEN TRUSS PANEL POINTS.

LOAD  
PANEL POINT

LOAD  
PANEL POINT

- MAXIMUM ALLOWABLE LOAD MUST BE LESSER OF RIGGING BEAM CAPACITY AND MAXIMUM ALLOWABLE CAPACITY OF TRUSS BOTTOM CHORD SHOWN IN THIS DRAWING.

- LOADS DUE TO PERMANENT ELEMENTS FASTENED TO THE TRUSSES AND RIGGING BEAMS MUST BE DEDUCTED FROM THE TOTAL PRODUCTION LOADS SHOWN IN THIS DRAWING.



THIS DRAWING IS THE SOLE PROPERTY OF IRC BUILDING SCIENCES GROUP AND MAY NOT BE REPRODUCED WITHOUT IRC GROUP'S WRITTEN CONSENT. © 2021

1	2021-11-26	ISSUED FOR CLIENT REVIEW	J.D.
No.	DATE	ISSUE	BY

**irc GROUP** **IRC BUILDING SCIENCES GROUP**  
A RIMKUS COMPANY  
2121 ARGENTIA ROAD, SUITE 401  
MISSISSAUGA, ONTARIO, L5N 2X4  
TEL:905.607.7244, FAX:905.607.7288  
1.888.607.5245 WWW.IRCGROUP.COM

PROJECT KITCHENER MEMORIAL AUDITORIUM  
CONCERT PRODUCTION LOAD STUDY

LOCATION 400 EAST AVENUE  
KITCHENER, ON

DESIGNER J.D.

DESCRIPTION  
ALLOWABLE PRODUCTION LOADS  
TRUSSES AND RIGGING BEAMS  
NO SNOW ON ROOF (SUMMER)

DATE	2021-11-26	JOB	100139351
SCALE	AS SHOWN	FILE	BS001
DRAWN BY	J.D.	SHEET	R-S03
CHECK BY	J.D.		

1 TRUSS BOTTOM CHORD ALLOWABLE  
LOAD CAPACITY PLAN (NO SNOW ON ROOF)  
R-S03 SCALE 3/32" = 1'-0"